

Technical data



EUROCAT CLASSIC Front mower with four drums

	Working width	Mounting	Placement width without swathing discs	2 / 4 Swathing discs
EUROCAT 271 CLASSIC	2.70 m	A-frame mounting	–	1.4 m / 0.9 m
EUROCAT 311 CLASSIC	3.05 m	A-frame mounting	–	1.4 m / 1.0 m
EUROCAT 311 PLUS CLASSIC	3.05 m	A-frame mounting	–	1.4 m / 1.0 m

EUROCAT ALPHA MOTION

EUROCAT 311 ALPHA MOTION MASTER	3.05 m	Cat. 2 / 2	–	1.4 m / 1.0 m
EUROCAT 311 ALPHA MOTION PRO	3.05 m	Cat. 2 / 2	–	1.4 m / 1.0 m
EUROCAT 311 ALPHA MOTION PLUS MASTER	3.05 m	Cat. 2 / 2	–	1.4 m / 1.0 m
EUROCAT 311 ALPHA MOTION PLUS PRO	3.05 m	Cat. 2 / 2	–	1.4 m / 1.0 m
EUROCAT 311 ALPHA MOTION PLUS ED PRO	3.05 m	Cat. 2 / 2	2.7 m – 1.9 m	–

EUROCAT Rear mower with four drums

EUROCAT 272	2.70 m	Cat. 2 / 2 and 3 / 3	1.8 m	1.4 m / 0.9 m
EUROCAT 272 ED	2.70 m	Cat. 3 / 3	1.6 m – 1.2 m	–
EUROCAT 312	3.05 m	Cat. 3 / 3	2.2 m	1.8 m / 1.4 m

Tractor PTO speed Transport width / height Power requirement from Hectares per hour up to Weight

1000 rpm	2.65 m	40 kW / 55 hp	2.7 ha/h	785 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	865 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	925 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	1025 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	1045 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	1065 kg
1000 rpm	3.0 m	44 kW / 60 hp	3.2 ha/h	1085 kg
1000 rpm	3.0 m	52 kW / 75 HP	3.2 ha/h	1285 kg
1000 rpm	3.60 m	52 kW / 75 hp	2.7 ha/h	1030 kg
1000 rpm	3.60 m	52 kW / 75 hp	2.7 ha/h	1290 kg
1000 rpm	3.80 m	59 kW / 80 hp	3.2 ha/h	1090 kg